



# FILTER TECHNOLOGY

cleaner fluids mean better business



Filtration and Contamination Control Specialists

## FM42043 Bulk Diesel Filtration Unit



### Features

- Flow rate 750 litre/min
- Pressure gauge on the inlet and outlet
- Live sample point on the inlet and outlet

### Filters

- 20 x FM3204 industrial filter units.

### Suitable for all:

- Diesel fuels

### Optional

- Can be trailer-mounted on request.
- RCI Pre-filter water separator
- Flow meter
- Isolation valves on the inlet and outlet
- 3" Camlock couplings

### Function

This bulk filtration unit can be used to filter diesel fuel contaminated with moisture, dust, rust, airborne contaminants, fungi and bacteria where the tanks have been treated with a biocide.

This unit can also be used as a remote filling station where fuel cleanliness cannot be guaranteed.

The filtration unit can be used as either a bulk delivery system or as an intermediate filtering system cleaning diesel from a bulk tank to a day tank. Both these scenarios require an existing pump set-up.

FM42043 Dimensions		
	Metric	US
Height	1350 mm	52"
Length	1200 mm	47"
Width	1400 mm	55"
Weight (wet)	700 kg	1543 lb
Max Pressure	5 bar	72 psi
Recommended operating pressure	3 bar	43 psi



Filter Technology Australia

Office: 44 Bonville Avenue, Thornton NSW 2322 • Postal: PO Box 101 Beresfield NSW 2322

Tel: +61 2 4966 1833 • Fax: +61 2 4966 1933 • Toll Free Australia: 1800 626 899

Email: info@filtertechnology.com.au • Web: www.filtertechnology.com.au

