



**FILTER
TECHNOLOGY**

cleaner fluids mean better business



Filtration and Contamination Control Specialists

FM40225D Bypass Filtration Unit

Designed to suit differential and final drive lube systems



Features

- Fitted with a pressure compensating flow control regulator on the inlet to the filters.
- Filter system operating pressure 3.1 – 3.5 bar (45 – 50 psi).
- 5 bar pressure gauge to indicate filter housing pressure.
- Live sample point.
- Non return valve on outlet.
- 5 bar check valve.

Filters

- 2 x FM3202 industrial filter housing.

Mounting

- Heavy duty powder coated frame.

Flow

- 3.0 litres/min (0.8 gal/min).

Function

For on-board filtration of differential, final drive and hydraulic systems.

FM 40225 Dimensions

	Metric	US
Height	650 mm	25.6"
Width	400 mm	15.7"
Depth	300 mm	11.2"
Weight	28 kg	61.7 lb
Max Pressure	5 bar	72 psi
Recommended operating pressure	3.5 bar	51 psi



Filter Technology Australia

Office: 44 Bonville Avenue, Thornton NSW 2322 • Postal: PO Box 101 Beresfield NSW 2322

Tel: +61 2 4966 1833 • Fax: +61 2 4966 1933 • Toll Free Australia: 1800 626 899

Email: info@filtertechnology.com.au • Web: www.filtertechnology.com.au

