



FM50462 Heavy Duty Filtration Buggy Pressure driven variable drive with heater



Features:

- Pressure driven variable drive
- Heated
- Fitted with pressure relief valve
- Pressure gauge.
- Hour run meter
- Element change light
- Pressure differential switch
- Emergency stop button
- Seven metres of hosing (3.5 m suction and 3.5 m return hoses)
- 3/4" quick release couplings
- Two wheeled, heavy duty trolley
- Mobile and portable
- Silicon filled tyres

Filters:

- 4 x FM3204 Industrial filter units
- Heated

Suitable for all:

- Gear oils
- Hydraulic oils

Option:

- On-board particle counter can be fitted on request.

Function

Oil Applications:

FTA Buggies are typically used for small hydraulic reservoirs on gearboxes, final drives, blow and injection moulder or wherever hydraulic oils are used. Their kidney loop system and quick release couplings allow easy movement between machines in industrial sites allowing machinery to be filtered while the machine is still in service. They can also be used to filter new oil from the drum into the machine.

FM50462 Dimensions

	Metric	US
Height	1390 mm	54.7"
Width	750 mm	29.5"
Depth	670 mm	26.3"
Weight	174 kg	384lb
Max Pressure	5 bar	72 psi
Recommended operating pressure	3 bar	43 psi